

Supa-Prime

Description

Supa-Prime is a new generation primer formulated to maximize penetration into a powdery oxidized roof tile to guarantee adhesion of Nutech top coat systems.

Supa-Prime has the remarkable ability to thoroughly wet and penetrate into difficult surfaces similar to a solvent based primer, without the disadvantages of solvent odours or high flammability. The resin system strengthens and binds the loose surface creating a strong and stable base for top coat systems

It is a tough flexible easy to use environmentally friendly water based primer specifically formulated to achieve maximum surface depth penetration and intercoat adhesion.

Supa-Prime is a non-yellowing clear primer, which is fully compatible with all Nutech top coat systems.

Typical Properties

Appearance:	Milky white viscous liquid
Total Solids Content:	20%
Per Cent Volatiles:	N/A
pH:	8.0
Specific Gravity:	1
Solubility In Water:	Soluble
Flammability	Non-flammable
Minimum Film Forming Temperature:	8°C.
Minimum Film Thickness (Dry Coat):	Subject to surface conditions
Recommended Application Rate:	One coat @ 5 square metres per litre

Applications & Features

Supa-Prime is manufactured from premium resins and surfactants to maximise performance under both cool and hot weather conditions. It is a stable non-yellowing coating, which retains both flexibility and strength with age. Supa-Prime provides excellent protection against bacteria and mould on most surfaces. Concrete and masonry surfaces undercoated with Supa-Prime require less top coat paint compared to an unsealed surface.

Supa-Prime has undergone rigorous testing and special consideration has been given to ensure that the chemical composition and compatibility with Nutech top coat systems is suitable for Australia and South-East Asian conditions. Features include:

- Fast drying speed
- Easy application by brush, roller or spray
- Guaranteed intercoat adhesion with Nu-Flex, TileFlex 2000®, NXT Cool Zone® and ColourFast
- 100% water and weather proof performance
- High resistance to mould and fungus
- Premium performance

Supa-Prime

- Excellent penetration through all oxidised powdery surfaces

Supa-Prime is also recommended for;

- Porous Concrete and Cinder Block walls
- Light weight concrete panels
- Tilt slab concrete walls
- Concrete render stucco and stucco-type wall finishes

Application Warnings

Do not spray apply on extremely hot surfaces which can restrict surface penetration. Apply in cooler weather conditions or pre-wet the roof with cold water to reduce the surface temperature in very hot weather. Heavy application is not required to maximise penetration through the powdery surface.

Refer to the Material Safety Data Sheet for additional safety and user information.

Important Note

The information given on this data sheet is based on many years experience and is correct to the best of our knowledge. However since the use of our product, surface conditions, weather and a number of other factors are completely beyond our control, we can only be responsible for the quality of our product at the time of dispatch. For more information please contact our Company. As this information is of a general nature, we cannot assume any responsibility in individual cases.