



Technical Data Sheet

NuFence

Product Description **NuFence** is an acrylic flat finish fence paint, excellent for rough sawn timber and picket fences.
NuFence is readily available in a select range of pre tinted contemporary colours with other colours available upon request.
NuFence has excellent covering power, low splatter and simple water clean-up.

- NuFence Features:**
- Low VOC and Low Odour
 - Hard wearing
 - Excellent adhesion
 - Easy application by brush, roller or spray
 - Easy cleaning
 - No primer or undercoat required

Safety Precautions: Observe all Occupation Health and Safety (OH&S) precautions. Refer to the relevant Safety Data Sheets (SDS) for product safety related information.
For further information and support: **Nutech Paint 03 9770 3000**
www.nutechpaint.com.au

Provisions: ***Do not apply in temperatures under 10°C or late in the day as the temperature can drop rapidly and the coating may not dry.***

In cold weather do not overcoat until the first coat is fully dried.
Avoid painting in high temperatures to avoid gloss damage and ensure surface adhesion and coating durability.

Chemical Type: Acrylic copolymer

Product Attributes PH: 8.5
Per Cent Volatiles (VOC): < 5%
Solubility: In Water
Minimum Film Forming Temperature: 10°C.

Typical Applications Typical projects include:
Domestic & Multi Density Residential, Industrial and Commercial applications.

Appearance White or colour tinted viscous liquid

Coverage / Spread Rate **8 to 10m²/L**
Note: Coverage will depend on the porosity and roughness of the surface.
To maximise performance do not over spread.

Packaging 10L and 20L

Storage / Shelf life Cool, dry location. Avoid contact with direct sunlight and heat
Stored 24 months @ 25°C



Substrate	NuFence is suitable for rough sawn timber and can also be used on picket fences.
Recommendations:	
Mixing/ Thinning	Prior to Commencement: Stir thoroughly prior to use. Maximum dilution: 10% with clean water
Test Patch	Conduct a small test patch in an inconspicuous area to ensure adequate product performance, substrate porosity and provide an indication of the time required to complete project.
Substrate note:	All surfaces must be clean and in sound condition. Remove all dirt, dust and flaking paint. <i>Improperly prepared surfaces may result in coating failure.</i>
Application	Brush Roller Airless Spray
Procedure:	Pre-painted surfaces: should be tested for compatibility and adhesion prior to over coating. Unpainted surfaces: Dilute first coat with 10% water to assist surface penetration and adhesion. For best results always apply 2 coats, extra coats may be applied as required. To make application easier in hot or windy conditions, the surface may be pre-wet, wipe off excess water before application.
Drying Time	Ambient conditions @ 25°C and 50% relative humidity. Touch Dry 20 Minutes.
Recoat	2 Hours. May be longer in cooler conditions or high humidity.
Clean Up	Protecting Our Environment is important to Nutech Paints: Clean up with cold water away from drains. Do not pour leftover paint down drains. Unwanted paint should be kept in a sealed container and then disposed of via special waste collection services. Empty paint containers should be left open in a well-ventilated area to dry out. Dispose of empty paint containers in accordance with local authority's guidelines. Always check with your local council first.
First Aid	SEEK IMMEDIATE MEDICAL ATTENTION. Refer to the appropriate <i>Nutech Material Safety Data Sheet</i> (MSDS) for further information. For medical emergencies only, call: 000 <ul style="list-style-type: none">• In case of eye contact, flush thoroughly with water for at least 15 minutes.• In case of skin contact, wash affected areas with soap and water. If irritation persists.• Remove and wash contaminated clothing.• If inhalation causes physical discomfort, remove to fresh air.• If discomfort persists, or any breathing difficulty occurs or if swallowed seek medical advice.



Warranty	<p>Nutech warrants its products to be free from defects in material and workmanship. Nutech's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at Nutech's option, to either replacement of products not conforming to this Warranty or credit to Buyer's account in the invoiced amount of the nonconforming products.</p> <p>Any claim under this Warranty must be made by Buyer to Nutech in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the delivery date, whichever is earlier. Buyer's failure to notify Nutech of such non-conformance as required herein shall bar Buyer from recovery under this Warranty.</p> <p>Nutech makes no other warranties concerning the product. No other warranties, whether express, implied, or statutory, such as warranties of merchantability or fitness for a particular purpose, shall apply. In no event shall Nutech be liable for consequential or incidental damages.</p> <p>Any recommendation or suggestion relating to the use of the products made by Nutech, whether in its technical literature, or in response to specific inquiry, or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by Buyers having requisite skill and know-how in the industry, and therefore it is for Buyer to satisfy itself of the suitability of the products for its own particular use and it shall be deemed that Buyer has done so, at its sole discretion and risk. Variation in environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results.</p>
Limitation of Liability	<p>Nutech's liability on any claim of any kind, including claims based upon Nutech's negligence or strict liability, for any loss or damage arising out of, connected with, or resulting from the use of the products, shall in no case exceed the purchase price allocable to the products or part thereof which gives rise to the claim. In no event shall Nutech be liable for consequential or incidental damages.</p>
Disclaimer	<p>The information given on this data sheet is based on many years' experience and is correct to the best of our knowledge. However, since the use of our product, surface conditions, weather and a number of other factors are completely beyond our control, we can only be responsible for the quality of our product at the time of dispatch. For more information please contact our Company. As this information is of a general nature, we cannot assume any responsibility in individual cases.'</p> <p>The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.</p>

Nutech

Nutech Paint
PTY LTD

☎ 03 9770 3000

✉ sales@nutech.com.au

www.nutechpaint.com.au